



SIZE (d)	D	C	G	T	N	M	L	H	W	W1	ISO 5211	E	Ma
125	254	216	186	23.9	8	22	358	224	750	24	F12	125	120
150	279	241.5	216	25.4	8	22	394	247	750	24	F12	125	180



TECHNICAL REQUIREMENTS

1. FACE TO FACE DIMENSION: ANSI B16.10
2. END FLANGE DIMENSION: ANSI B16.5
3. TEST: API 598
4. BLOW-OUT PROOF STEM / FULL PORT
5. WITH ISO 5211 MOUNTING PAD
6. INVESTMENT CASTING BODY
7. LOCKING DEVICE



TEST PRESSURE:

SHELL(BY WATER)	450PSI
	32kg/cm ²
SEAT	315PSI
	22kg/cm ²
BY AIR	85PSI
	6kg/cm ²

NO.	PART	MATERIAL
1	BODY	ASTM A351 CF8M
2	CAP	ASTM A351 CF8M
3	BALL	ASTM A351 CF8M
4	SEAT	PTFE
5	STEM	SUS 316
6	GASKET	PTFE
7	THRUST WASHER	PTFE
8	PACKING	PTFE
9	STEM PACKING	PTFE
10	GLAND	ASTM A351 CF8
11	GLAND BOLT	SUS 304
12	HANDLE	WCB
13	STOPPER	SUS 304
14	SNAP RING	SUS 304
15	BOLT	SUS 304
16	HANDLE BOLT	SUS 304
17	PLASTIC COVER	PLASTIC

REV	C	BROOK VALVES	
DATE	NOV 2010	V2F-150	
SCALE	TO FIT		
316SS BALL VALVE FB CLASS 150 LEVER OP			