



DESIGN & MFT	ASME B16.34	END CONNECTIONS	R.F
PRE-TEMP RATING	ASME B16.34	INSPECT & TEST	API 598
F-F DIMENSION	ASME B16.10	FLANGED DIMENSION	ASME B16.5
MARKING	NA	FIRE SAFE DESIGN	NA
PAINTING	BARE FINISH	LOGO	BV IN A CIRCLE

TEST PRESSURE Mpa		
API 598	SHELL	SEAT
HYDROSTATIC	3.1	2.2
AIR		



SIZE	L	d	H	D	C	G	f	T	N-ØM
15	108	15	51	89	60.5	35	1.6	11.1	4-ø16
20	117	20	54	98	70	43	1.6	11.1	4-ø16
25	127	25	64	108	79.5	51	1.6	11.1	4-ø16
32	140	32	68	117	89.5	64	1.6	12.7	4-ø16
40	165	40	75	127	98.5	73	1.6	14.3	4-ø16
50	203	50	97	152	120.5	92	1.6	15.9	4-ø19
65	216	65	111	178	139.5	105	1.6	17.5	4-ø19
80	241	80	120	190	152.5	127	1.6	19.1	4-ø19
100	292	100	162	229	190.5	157	1.6	23.9	8-ø19
125	330	125	179	254	216	186	1.6	23.9	8-ø22
150	356	150	203	279	241.5	216	1.6	25.4	8-ø22
200	495	200	236	343	298.5	270	1.6	28.6	8-ø22
250	622	250	302	406	362	324	1.6	30.2	12-ø25
300	698	300	340	483	432	381	1.6	31.8	12-ø25
350	787	350	385	533	476.5	413	1.6	35	12-ø25



NO.	PART NAME	MATERIAL
1	BODY	A351 CF8M
2	DISC	A351 CF8M
3	NUT	SUS 316
4	ARM HINGE	A351 CF8M
5	HINGE PIN	SUS 316
6	GASKET	PTFE
7	BONNET	CF8M
8	SPRING WASHERS	SUS 304
9	BONNET BOLT	SUS 304
10	BOLT	SUS 304
11	DISC CAP	A351 CF8M
12	BOLT	SUS 304

REV	B	<h2 style="margin: 0;">BROOK VALVES</h2> <h3 style="margin: 0;">VSC-150</h3> <p style="margin: 0;">STAINLESS STEEL SWING CHECK CLASS 150 RF</p>
DATE	Jan-20	
SCALE	TO FIT	