



SIZE	L	°1	°2	n-d	°3	b
350	381	520	470	12 - 26	438	26.5
400	406	580	521	12 - 26	489	28
450	432	640	584	16 - 26	552	30
500	457	705	641	16 - 26	609	31.5
600	508	825	756	16 - 33	717	36

SPECIFICATIONS	
CLASS	PN 16
DESIGN	BS 5163
FACE TO FACE	BS 5163
END FLANGE	AS 2129 TABLE E
TEST	BS 6755 PART 1
WORKING TEMP	60°C

ITEM	PART NAME	MATERIAL
1	BODY	DUCTILE IRON GGG40
2	SEAT	EPDM
3	SHAFT	SS316
4	DISC	GGG40 + EPDM
5	WEDGE NUT	BRASS
6	BONNET GASKET	EPDM
7	NUT	A2-70
8	BONNET	DUCTILE IRON GGG40
9	O RING	EPDM
10	SEALING RING	BRASS
11	THRUST WASHER	A2-70
12	HANDWHEEL	Q235

BROOK VALVES		
REV	B	RSG TABLE E CLASS PN 16
DATE	Aug-20	
SCALE	TO FIT	
DI RESILIENT SEATED NON-RISING STEM WEDGE GATE VALVE		