



SIZE	L	D	D1	D2	b	f	n - ød	W
15	130	95	65	45	16	2	4-ø14	140
20	150	105	75	58	18	2	4-ø14	140
25	160	115	85	68	18	2	4-ø14	160
32	180	140	100	78	18	2	4-ø18	160
40	200	150	110	88	18	3	4-ø18	180
50	230	165	125	102	20	3	4-ø18	200

Performance Specification			
Nominal Pressure		PN40	
Test Pressure	Strength	6.0	Mpa
	Sealing	4.4	
	Air	0.6	
Suit medium: Water-Steam-Oil etc.			



NO.	PART NAME	MATERIAL
1	BODY	GS-C25
2	SEAT	GS-C25+13Cr
3	DISC	13Cr
4	PIN	SS304
5	STEM	2Cr13
6	BELLOWS	SS304
7	SEALING MEMBER	SS304
8	GASKET	SS304+GRAPHITE
9	BONNET	GS-C25
10	BOLT	A193 B7
11	NUT	A194 2H
12	PACKING	GRAPHITE
13	THREADED GLAND	A105
14	PIN	65Mn
15	LOCATOR	1025
16	STEM NUT	1045
17	OIL CAP	COPPER
18	HANDWHEEL	1025
19	CAP	A105

DESIGN & MFT	EN12516	END CONNECTIONS	R.F
Max Desgin Temp	425°C	INSPECT & TEST	EN12266
F-F DIMENSION	EN558	FLANGED DIMENSION	EN1092
PAINTING	STD SILVER	LOGO	BV IN A CIRCLE

REV	A	<h2>BROOK VALVES</h2> <h3>BSGLDIN40</h3> <p>BELLOW SEALED GLOBE VALVE OS&amp;Y DIN 40 RF</p>
DATE	Jan-21	
SCALE	TO FIT	