


NO.	PART NAME	MATERIAL
1	BODY	CAST IRON (GG25)
2	BUSHING	PTFE
3	O-RING	NBR (NITRILE)
4	STEM	SS 410
5	DISC	SS 316
6	SEAT	EPDM
7	PIN	SS 316

700mm (28") - 1200mm (48") WAFER
TABLE E BUTTERFLY VALVES GEAR
OPERATED ONLY

FUSION BONDED EPOXY (FBE)
COATING BLUE BODY COLOUR
STAINLESS DISC



SIZE	L	D1	n-Ød1	D2	c	H	H1	H2	H3	ØE	ØE1	8-Ød0	ISO	Gear Ratio	Torque (Nm)
700	162	845	20-Ø33	695	63.35	1129	33	624	66	300	254	8-Ø18	F25	680:1	4602
750	166	927	20-Ø36	744.6	63.35	1145	33	646	66	300	254	8-Ø18	F25	680:1	4717
800	187	984	20-Ø36	794.7	63.35	1248	35	672	66	300	254	8-Ø18	F25	680:1	4931
900	202	1092	24-Ø36	864.7	75	1357	35	720	118	300	254	8-Ø18	F25	704:1	5917
1000	215	1175	24-Ø39	965	85	1501	35	800	142	300	254	8-Ø18	F25	704:1	6528
1200	276	1410	32-Ø39	1165	105	1784	35	941	160	350	298	8-Ø22	F30	850:1	9214

REV	E	BROOK VALVES	
DATE	Jan-21	WEEG	
SCALE	TO FIT		
CAST IRON WAFER TABLE E BUTTERFLY VALVE 10 BAR RATED			