



**FEATURES:**

- SUPER DUPLEX UNS S32750
- BLOW-OUT PROOF STEM
- DIRECT MOUNTING PAD ISO 5211
- 1000 PSI WOG (63 BAR)

**SUPER DUPLEX UNS S32750**


SIZE	L	H	W	H1	H2	ØA	ØB	M1	M2	□Q	TORQUE (NM)	WEIGHT (Kg)
15	55	64	112	38	8.3	42	—	Ø6	—	9	5.5	0.34
25	82.5	74	138	44.4	11	42	50	R3	R3.5	11	11	0.79
40	103	96	205	59.5	15	50	70	R3.5	R4.5	14	24	1.96
50	120	104	205	67	15	50	70	R3.5	R4.5	14	33	2.59



ANTI-STATIC DEVICE



NO.	PART NAME	MATERIAL
1	BODY	2507-UNS S32750
2	CAP	2507-UNS S32750
3	BALL	F53
4	BALL SEAT	PTFE
5	JOINT GASKET	PTFE
6	STEM	S32750
7	THRUST WASHER	PTFE
8	O-RING	VITON
9	STEM PACKING	2PTFE
10	STEMRING	AISI 304
11	BELLEVILLE WASHER	AISI 301
12	STEM NUT	AISI 304
13	STOPPER	AISI 304
14	HANDLE	AISI 304
15	HANDLE SLEEVE	PLASTIC
16	LOCK WASHER	AISI 304



REV	A	<b>BROOK VALVES</b>  <b>V2MH</b>  2-PCe SUPER DUPLEX BALL VALVE FB BSP ENDS with ISO MOUNTING PAD
DATE	Dec-22	
SCALE	TO FIT	